

MACHINE TRANSLATION FEEDBACK FORM

Please fill out this form after reviewing your machine translation and return to Translations Branch, STIC, CP3/4. This information will help us determine the effectiveness of providing machine translations.

Filling out this form is entirely voluntary, and all information will be used solely by the Translations Branch for information purposes.

1. How much time did you spend reviewing the machine translation?
2. Did you find what you were looking for in the machine translation, or did you also request an oral translation for clarification?
3. Did you find that having a machine translation saved you time?
4. Please provide any other comments or suggestions.

**STIC Translations Branch is now offering Machine Translated
Japanese Patent Documents to all Technology Centers**

- The advantage of machine translation is faster turnaround time and lower costs.
- Presently, machine translation is available for Japanese Unexamined A (Kokai) documents 1993 onward and Japanese Patent B documents 1994 and onwards.
- **When submitting your request for a Japanese document, it is important to clearly indicate if the requested document is an A or B document because the Japanese patent system reuses patent numbers.**
- The vendor is supplying machine translations which have been reviewed by language and art area experts. However, at times, the sentence structure and syntax of machine translations can be awkward. When in doubt, please call one of the STIC Japanese translators for clarification. Their contact information is included here.
- We will continue to check if an English-language equivalent is available prior to processing a request and encourage using it, when possible.
- The attachments below provide additional information about the process and the service.
- **Unless otherwise indicated, STIC will process requests from alt TC's which meet these guidelines, as machine translation requests.**

We welcome your feedback; included is an evaluation form which can be dropped off at the Translations Branch, or e-mailed to STIC-Translations Box.

John Graham
Branch Chief
Translations

Arti Shah
Division Chief
STIC

Kristin Vajs
Director
STIC

Attachments:

-Request Form:

-Machine Translation Information/Background:

-Internet Sites as Sources for Translations:

Note: Unexamined Japanese A (Kokai) documents can be viewed for free at the Japanese Web site: http://www.ipdl.jpo-miti.go.jp/homepg_e.ipdl. The translations are raw machine translations.

- Evaluation Form:

Translation Staff Information:

JOHN R. GRAHAM-Supervisor	- Room 103 - 308-3293
AKIKO SMITH	- Room 108 - 308-3244
JOHN M. KOYTCHIEFF	- Room 106 - 308-1185
MARTHA WITEBSKY	- Room 104 - 308-3282
STEVEN SPAR	- Room 105 - 308-3281
MATTHEW ALT	- Room 109 - 305-3530
CHISATO MOROHASHI	- Room 107 - 308-3279

Guidelines for Use of Machine Translations of Japanese Patents

Machine translations are an excellent, cost effective, rapid way of determining the information presented in a patent and identifying patents which are relevant. It is the quickest way to determine the essence of a particular foreign language document, i.e. "gisting". Machine translation is often used as a tool to aid human indexers by saving time spent in terminology lookups.

Approximately 27% of the requests for translation received in STIC are for Japanese patents from 1993 onwards. A few vendors have started offering machine translation of Japanese patent documents. The pilot indicated this type of service can play a role in helping examiners determine the basic information in Japanese patent.

Machine translation will help control translation costs, will improve the timeliness of translations, and in most cases provide an adequate product. Some machine translated patents or parts of patents will require human oral or written translation at a later point.

The following information is provided as background. Please keep these points in mind when using machine translations.

- When one has numerous Japanese documents submitted by an applicant, the MT product may prove sufficient to determine the basic information when the examiner considers it necessary to do so. Machine translation is good for determining if certain concepts or words appear in the patent and in providing an overall look at the content of the patent. STIC does not recommend its use in a court of law, unless consultation with a STIC translator has taken place.
 - The meanings of words can be context-bound and the syntax is not always clear in machine translated text. The translated sentence structure may be confusing to interpret. The qualities of translations are good from the standpoint of terminology; grammar is often weak, but improving. When in doubt, a translator should be contacted. When a response to a rejection raises questions about the content of a foreign reference, the examiner should obtain at least a partial written translation of the portions in question.
 - Any portion of a reference relied upon for a final rejection or appeal should be confirmed by a human translator, even if it is only a confirmation by a human translator of the accuracy of the MT translation. The confirmed translation of a disputed portion should preferably be included in the next office action.
 - We will be using Human Assisted Machine Translations (MATS). MATS are an automated translation of text, using complex technology, from one natural language to another, by a computer. The translation is reviewed by human translators. The MAT gives a quick idea of the content of the patent document, is cost effective and offers a quicker turnaround. The pilot vendor, Derwent promises 5-day turnaround time from the point their Japanese Office receives the request. STIC monitors their performance. Requests are transmitted to the Derwent US office by STIC after initial processing.
 - The format of the machine translated documents provided -two columns of the original Japanese text and the English translation-is designed to facilitate the accurate selection of content for follow-up custom translation.
-
-



Home | STIC Catalog | Site Guide | EIC | Automation Training/ITRPs | Contact Us | STIC Staff | FAQ | Firewall Authentication

Scientific and Technical Information Center

Patent Intranet > NPL Virtual Library > Translation Services > Internet Translation Tools

[Site
Feedback](#)

[NPL Home](#) | [STIC Catalog](#) | [Site Guide](#) | [EIC](#) | [Automation Training/ITRPs](#) | [Contact Us](#) | [STIC Staff](#) | [FAQ](#) | [Firewall Authentication](#)

Internet Translation Tools

There are many tools available over the Internet which may be useful to you when you need a quick answer to the meaning of a particular word or phrase in a foreign language. Below you will find a list of Internet sites that are used as additional tools by some of the STIC translators and may be useful to you. However, caution should be exercised when using any of these tools. The specific subject matter and context in which a given term or expression is used will frequently determine how it should be translated into English. Most online dictionaries do not provide an adequate number of alternative translations for a given term or subject matter-specific examples of usage.

For technical translations for various languages:
<http://europa.eu.int/eurodicautom/login.jsp>

For non-technical terminology use:
<http://www.logos.it/dictionary>

A good source for multi-lingual glossary links with emphasis on German:
<http://www.jump.net/~fdietz/glossary.htm>

For German, French, Spanish, Portuguese and Italian:
<http://babelfish.altavista.com>

Another site for raw Machine Translations of Japanese Patents:
http://www.ipdl.jpo.go.jp/homepg_e.ipdl

Additional sites include:
<http://translator.dictionary.com/text.html>
<http://www.facstaff.bucknell.edu/rbeard/diction.html>

If you have any questions about this information, feel free to call the Translations Branch at 308-0881 or one of the translators on staff. To see a list of the translators, their background and experience as well as their phone numbers and location, [click here](#).

Submit comments and suggestions to [John Graham](#)

To report technical problems, [click here](#)

[Intranet Home](#) | [Index](#) | [Resources](#) | [Contacts](#) | [Internet](#) | [Search](#) | [Firewall](#) | [Web Services](#)

Last Modified: Wed, 12 Feb 2003 18:07:05 GMT

Translation of French Patent Document No. 2,129,807.

Inventor: Pierre Avril et al.

Applicant: Jeumont-Schneider

Int. Cl: G01 g 11/00

Priority Date: N/A

Date of Application: March 15, 1971

Date of Publication: November 3, 1972, B.O.P.I. "Listes"

Original French Title: Procédé et despositif de pesage continu de charges sur un transporteur à bande.

METHOD AND DEVICE FOR CONTINUOUSLY WEIGHING LOADS ON A CONVEYOR BELT

The present invention relates to a method and device for continuously weighting loads on a conveyor belts which eliminates the influence of the conveyor belt on the weighed quantity.

It is known that in weighing systems for loads of loose bulk material transported on a conveyor belt, such as the systems used especially on extraction-measuring feeders, a portion of the loaded conveyor is weighed by ~~arranging between two support rollers or between two cylinders an~~ intermediary roller which is supported by a lever which acts as a scale

member.

Since, on in the course of this weighing operation not only a certain portion of the load, but also the section of the belt which serves as the receptacle of the load is weighed and since this weight is not insignificant, the result is that the precise net weight of the load is not known.

In fact, the major portion of weighting error is due to the variations in weight of the conveyor belt and to deposits of dust on the levers of the load weighing system. It is therefore appropriate to permanently counterbalance the conveyer belt.

However, known continuing weighing apparatuses do not allow such counterweight to be permanently carried out. Rather, it is accomplished in an intermittent manner by freeing the belt of all materials and rotating the latter empty for a predetermined number of complete revolutions in order to allow the operator to compensate for the effects of accumulation or wear by means of a mechanical or electrical auxiliary device and to return the weight of the belt to the original value at the start of the weighing process.

This operation requires a certain length of time, and the major drawback is having to stop the transport of the product on the belt during the counterweighing operation or to stop the installations to which the belt is

connected.

It is the object of the present invention to provide a process and a device which allows to remedy this drawback by permanently compensating possible variations in the weight of the conveyor belt, and to accomplish this without the movement of the products on the belt.

The invention relates primarily to a continuous weighing process of loads on a conveyor belt in which, in addition to the normal measurement of the weight on the loaded belt, the weight of the belt is also measured at one point on the empty return trip, and the latter measure is subtracted from the weight on the loaded belt.

The invention also relates to the device using this method, i.e., a continuous weighing device for loads on a conveyor belt which is equipped with a continuous weighing system for the loaded belt and comprising, on the one hand, in association with said weighing system, a second continuous weighing system which is arranged at a point along the return path of the empty belt and measuring the actual weight of the empty belt and, on the other hand, means for subtracting the second weight from the first in such a way as to permanently compensate for the possible variations in weight of the conveyor belt.

The invention will be better understood with help of the embodiment and the accompanying drawing in which the sole Figure illustrates an extraction-measuring feeder for loose bulk materials, although the invention is applicable to any other continuous weighing apparatuses as well.

The extraction-measuring feeder comprises two cylinders 1 and 2 which are mounted on a non-illustrated chassis. One of the cylinders 1 is driven by a variable-speed motor M.

The endless conveyor belt 3 runs over two cylinders, which ensure the extraction of the products **P** at different quantities by means of the hopper 4, and moves these products in the direction of the arrow **f** between the two cylinders 1 and 2. Downstream of the hopper 4, a weighing member is arranged which comprises a weighing roller 5, which is subjected to the weight on the loaded belt 3 and is supported on a lever 6 which pivots about a fixed shaft 7 and transmits the force to a stationary sensor 8 which emits an electrical signal proportional to the force applied to the weighing roller 5.

A similar system having identical features to the one described above, but marked with the letter **a**, are disposed on the return path 3a of the empty belt and transmit to a sensor 8a the effort exerted by the empty belt on the roller/weighing unit 5a.

The display of sensor 8a is fed from that of sensor 8 into a known subtraction member 9 and permanently displays the net weight of the load or of the loose bulk material **P** that is being transported by the conveyor belt 3.

The weighing members illustrated schematically in the drawing have merely been described as non-limiting examples. Any other known weighing devices allowing the practical realization of such a subtraction of measurements may also be utilized.

The invention does not only apply to extraction-measuring feeder but also to weighing machines with subtraction devices and flow meters.

CLAIMS

1. Method for continuously weighing loads on a conveyor belt in which, in addition to the normal continuous measurement of the weight on the loaded belt, the continuous measure of the weight of the belt is measured at a point along the empty return path, and this latter measurement is subtracted from that of the weight of the loaded belt.

2. A continuous weighing device for loads on a conveyor belt which is equipped with a continuous weighing system for the loaded belt and comprises, on the one hand, in association with said weighing system, a

second continuous weighing system which is arranged at a point along the return path of the empty belt and measures the actual weight of the empty belt and, on the other hand, means for subtracting the second weight from the first in such a way as to permanently compensate for the possible variations in weight of the conveyor belt.

US Patent and Trademark Office
S.T.I.C. Translations Branch
Martha Witebsky - March 12, 2001

Translation of French Patent Document No. 2,129,807

Inventor: Pierre Avril et al.

Applicant: Jeumont-Schneider

Int. Cl: G01 g 11/00

Priority Date: N/A

Date of Application: March 15, 1971

Date of Publication: November 3, 1972, B.O.P.I. "Listes"

Original French Title: Procédé et dispositif de pesage continu de charges sur un transporteur à bande.

METHOD AND DEVICE FOR CONTINUOUSLY WEIGHING LOADS
ON A CONVEYOR BELT

The present invention relates to a method and device for continuously weighting loads on a conveyor belts which eliminates the influence of the conveyor belt on the weighed quantity.

It is known that in weighing systems for loads of loose bulk material transported on a conveyor belt, such as the systems used especially on extraction-measuring feeders, a portion of the loaded conveyor is weighed by arranging between two support rollers or between two cylinders an intermediary roller which is supported by a lever which acts as a scale member.

Since, on in the course of this weighing operation not only a certain portion of the load, but also the section of the belt which serves as the receptacle of the load is weighed and since this weight is not insignificant, the

result is that the precise net weight of the load is not known.

In fact, the major portion of weighting error is due to the variations in weight of the conveyor belt and to deposits of dust on the levers of the load weighing system. It is therefore appropriate to permanently counterbalance the conveyor belt.

However, known continuing weighing apparatuses do not allow such counterweight to be permanently carried out. Rather, it is accomplished in an intermittent manner by freeing the belt of all materials and rotating the latter empty for a predetermined number of complete revolutions in order to allow the operator to compensate for the effects of accumulation or wear by means of a mechanical or electrical auxiliary device and to return the weight of the belt to the original value at the start of the weighing process.

This operation requires a certain length of time, and the major drawback is having to stop the transport of the product on the belt during the counterweighing operation or to stop the installations to which the belt is connected.

It is the object of the present invention to provide a process and a device which allows to remedy this drawback by permanently compensating possible variations in the weight of the conveyor belt, and to accomplish this without the movement of the products on the belt.

The invention relates primarily to a continuous weighing process of loads on a conveyor belt in which, in addition to the normal measurement of the weight on the loaded belt, the weight of the belt is also measured at one point on the empty return trip, and the latter measure is subtracted from the weight on the loaded belt.

The invention also relates to the device using this method, i.e., a continuous weighing device for loads on a conveyor belt which is equipped

with a continuous weighing system for the loaded belt and comprising, on the one hand, in association with said weighing system, a second continuous weighing system which is arranged at a point along the return path of the empty belt and measuring the actual weight of the empty belt and, on the other hand, means for subtracting the second weight from the first in such a way as to permanently compensate for the possible variations in weight of the conveyor belt.

The invention will be better understood with help of the embodiment and the accompanying drawing in which the sole Figure illustrates an extraction-measuring feeder for loose bulk materials, although the invention is applicable to any other continuous weighing apparatuses as well.

The extraction-measuring feeder comprises two cylinders 1 and 2 which are mounted on a non-illustrated chassis. One of the cylinders 1 is driven by a variable-speed motor M.

The endless conveyor belt 3 runs over two cylinders, which ensure the extraction of the products P at different quantities by means of the hopper 4, and moves these products in the direction of the arrow f between the two cylinders 1 and 2. Downstream of the hopper 4, a weighing member is arranged which comprises a weighing roller 5, which is subjected to the weight on the loaded belt 3 and is supported on a lever 6 which pivots about a fixed shaft 7 and transmits the force to a stationary sensor 8 which emits an electrical signal proportional to the force applied to the weighing roller 5.

A similar system having identical features to the one described above, but marked with the letter a, are disposed on the return path 3a of the empty belt and transmit to a sensor 8a the effort exerted by the empty belt on the roller/weighing unit 5a.

The display of sensor 8a is fed from that of sensor 8 into a known

subtraction member 9 and permanently displays the net weight of the load or of the loose bulk material **P** that is being transported by the conveyor belt 3.

The weighing members illustrated schematically in the drawing have merely been described as non-limiting examples. Any other known weighing devices allowing the practical realization of such a subtraction of measurements may also be utilized.

The invention does not only apply to extraction-measuring feeder but also to weighing machines with subtraction devices and flow meters.

CLAIMS

1. Method for continuously weighing loads on a conveyor belt in which, in addition to the normal continuous measurement of the weight on the loaded belt, the continuous measure of the weight of the belt is measured at a point along the empty return path, and this latter measurement is subtracted from that of the weight of the loaded belt.

2. A continuous weighing device for loads on a conveyor belt which is equipped with a continuous weighing system for the loaded belt and comprises, on the one hand, in association with said weighing system, a second continuous weighing system which is arranged at a point along the return path of the empty belt and measures the actual weight of the empty belt and, on the other hand, means for subtracting the second weight from the first in such a way as to permanently compensate for the possible variations in weight of the conveyor belt.

US Patent and Trademark Office
S.T.I.C. Translations Branch
Martha Witebsky - March 12, 2001

①⑨ RÉPUBLIQUE FRANÇAISE

INSTITUT NATIONAL
DE LA PROPRIÉTÉ INDUSTRIELLE

PARIS

①① N° de publication :

2.129.807

(A utiliser que pour
le classement et les
commandes de reproduction.)

②① N° d'enregistrement national :

71.08860

(A utiliser pour les paiements d'annuités,
les demandes de copies officielles et toutes
autres correspondances avec l'I.N.P.I.)

①③
DEMANDE
DE BREVET D'INVENTION

1^{re} PUBLICATION

②② Date de dépôt 15 mars 1971, à 11 h 45 mn.

④① Date de la mise à la disposition du
public de la demande..... B.O.P.I. — «Listes» n. 44 du 3-11-1972.

⑤① Classification internationale (Int. Cl.) G 01 g 11/00.

⑦① Déposant : JEUMONT-SCHNEIDER, résidant en France.

Titulaire : *Idem* ⑦①

⑦④ Mandataire :

⑤④ Procédé et dispositif de pesage continu de charges sur un transporteur à bande.

⑦② Invention de : Pierre Avril et Henri Niclas.

③③ ③② ③① Priorité conventionnelle :

Vente des fascicules à l'IMPRIMERIE NATIONALE, 27, rue de la Convention - PARIS (15^e)

L'invention concerne un procédé et un dispositif de pesage continu de charges sur un transporteur à bande, dans lequel on élimine l'influence du poids de la bande transporteuse sur la pesée.

5 On sait que dans les systèmes de pesage continu de charges ou de produits en vrac véhiculés sur un transporteur à bande, systèmes utilisés notamment dans le cas des extracteurs-doseurs continus, on procède à la pesée d'un tronçon de bande chargé en disposant entre deux rouleaux supports ou entre deux tambours un
10 rouleau intermédiaire dit rouleau-peseur qui prend appui sur un levier actionnant un organe de pesée.

Comme au cours d'une telle pesée on mesure non seulement une certaine portion de la charge mais également le tronçon de bande qui lui sert de réceptacle et dont le poids n'est pas négligeable, il en résulte que le poids net de la charge n'est pas connu avec une grande précision.

En effet, la majeure partie des erreurs de pesée est due aux variations de poids de la bande transporteuse, variations dues à l'encrassement ou à l'usure de ladite bande et aux dépôts de
20 poussières sur les leviers du système de pesage des charges. Il conviendrait donc de tarer en permanence la bande transporteuse.

Or, avec les appareils connus de pesage continu, un tel tarage ne peut pas être effectué en permanence; il se fait de façon intermittente en vidant la bande de toutes matières et en
25 faisant tourner cette dernière à vide pendant un certain nombre de révolutions complètes afin de permettre à un opérateur de compenser les effets de l'encrassement ou de l'usure par un dispositif auxiliaire mécanique ou électrique et de ramener le poids de la bande à sa valeur d'origine au début de la pesée.

30 Cette opération nécessite un certain temps et a comme inconvénient majeur l'arrêt de l'écoulement du produit sur la bande pendant tout le tarage, d'où l'arrêt correspondant des installations auxquelles la bande est liée.

Le but de la présente invention est de fournir un procédé et un dispositif permettant de pallier cet inconvénient grâce à une compensation permanente des variations éventuelles de
35 poids de la bande transporteuse et cela sans arrêter l'écoulement de produits sur ladite bande.

L'invention concerne tout d'abord un procédé de pesage
40 continu de charges sur un transporteur à bande dans lequel, outre

la mesur normale continue du poids de la bande chargée, on effectue la mesure du poids de la bande en un point de son chemin de retour à vide, et la soustraction de cette dernière mesure à celle du poids de la bande chargée.

5 L'invention concerne également le dispositif utilisant ce procédé, c'est-à-dire un dispositif de pesage continu de charges sur un transporteur à bande, muni d'un système de pesage continu de la bande chargée et comportant d'une part, en association avec ledit système de pesage, un second système de pesage continu
10 disposé en un point du chemin de retour à vide de ladite bande et mesurant le poids réel de la bande vide, d'autre part des moyens pour soustraire la seconde pesée de la première, de manière à compenser en permanence les variations éventuelles de poids de la bande transporteuse.

15 L'invention sera mieux comprise à l'aide d'un exemple de réalisation et du dessin annexé dont la figure unique représente schématiquement un extracteur-doseur de produits en vrac, bien que l'invention soit applicable à tous autres appareils de pesage continu.

20 L'extracteur-doseur est constitué par deux tambours 1 et 2 montés sur un châssis non représenté sur le dessin. L'un des tambours 1 est entraîné par un moteur M à vitesse variable.

La bande sans fin 3 défilant sur les deux tambours assure l'extraction des produits P à doser déversés par la trémie 4,
25 et véhicule ces produits dans le sens de la flèche f entre les deux tambours 1 et 2. En aval de la trémie 4 est situé un organe peseur constitué par un rouleau peseur 5 soumis au poids de la bande chargée 3 et prenant appui sur un levier 6 articulé autour d'un axe fixe 7 et transmettant l'effort à un capteur fixe 8 émet-
30 tant un signal électrique proportionnel à l'effort appliqué sur le rouleau-peseur 5.

Un système semblable, dont les repères correspondants sont les mêmes que précédemment mais affectés de l'indice a, est disposé sur le chemin de retour 3a de la bande à vide et transmet
35 à un capteur 8a l'effort exercé par la bande à vide sur le rouleau-peseur 5a.

L'indication du capteur 8a est retranchée de celle du capteur 8 dans un organe soustracteur 9 de type connu indiquant en permanence le poids net de la charge ou des produits en vrac
40 P véhiculés par la bande transport us 3.

Les organes-peseurs représentés schématiquement sur le dessin n'ont été décrits qu'à titre d'exemple non limitatif. Tout autre organe peseur de type connu permettant la réalisation pratique d'une telle soustraction des mesures de poids peut également être utilisé.

L'invention s'applique non seulement à des extracteurs-doseurs, mais également à des balances intégratrices et des débitmètres, par exemple.

REVENDICATIONS

- 1.- Procédé de pesage continu de charges sur un transporteur à bande dans lequel, outre la mesure normale continue du poids de la bande chargée, on effectue la mesure continue du poids de la bande en un point de son chemin de retour à vide et la soustraction de cette dernière mesure à celle du poids de la bande chargée.
- 5
- 2.- Dispositif de pesage continu de charges sur un transporteur à bande, muni d'un système de pesage continu de la bande chargée, caractérisé en ce qu'il comporte d'une part, en association avec ledit système de pesage, un second système de pesage continu disposé en un point du chemin de retour à vide de ladite bande et mesurant le poids réel de la bande vide, d'autre part des moyens pour soustraire la seconde pesée de la première de manière à compenser en permanence les variations
- 10
- 15 éventuelles de poids de la bande transporteuse.

